

Benelli

STRENGTH UPON STRENGTH

Benelli's muscular new 752S is here to shake up the sport naked balance of power



752^S



GREEN

SPECIFICATIONS

ENGINE

Type
2-cylinder/4-stroke/8-valve
Valve Train
DOHC
Bore & Stroke
ø88 x 62 mm.
Displacement
750 c.c.
Rated Output
56kw/8500rpm/min
Compression Ratio
11.5:1
Gearbox
6-speed
Lubrication
Pressure splash lubrication
Clutch
Wet multi-plate
Fuel System
EFI
Exhaust System
Long-acting Catalyst and Oxygen Sensor
Starting
Electric
Cooling System
Water-cooled
Ignition
TLI

752S

CHASSIS

Frame
Arch bar truck
Front Suspension
50mm Marzocchi forks, 130 mm stroke.
Rear Suspension
KYB Telescopic coil spring oil damped, 60 mm.
Front Brake
Dual Brembo discs, diameter 320 mm.
Rear Brake
Brembo Disc, diameter 260 mm.
Front Wheel
17 x 3.5 inch
Rear Wheel
17 x 5.5 inch
Front Tire
120/70ZR17
Rear Tire
180/55ZR17
Wheelbase
1460 mm.
Ground Clearance
180 mm.
Dry Weight, unladen
217 Kg.
Fuel Capacity
14.5 L.



BLACK



RED



WHITE



@benelli_au_nz

www.benelli.com.au

PURE PASSION SINCE 1911

